## CLAIMS

## What is claimed is:

- A flow restrictor for a medical aspiration system, 1 1.
- 2 comprising:

- a filter housing; 3
- a flow restrictor coupled to said filter housing; and, 4
- a filter located within said filter housing. 5
- TOULLY LEELEL The flow restrictor of claim 1, wherein said flow 2.
  - restrictor has a diameter between 0.1 to 1 millimeters.
  - The flow restrictor of claim 1, wherein said flow 3.
  - restrictor is located within an output luer attached to 2
  - said filter housing. 3
  - The flow restrictor of claim 3, wherein said output 1
  - luer includes a scaling insert. 2
  - An aspiration tube assembly for a medical system, 1
  - comprising: 2
  - an input tube; 3

BJY/wrj

- an input luer coupled to said input tube, said input
- 5 luer having a diameter;
- a filter housing coupled to said input luer;
- 7 a filter located within said filter housing, said
- 8 filter having a diameter that is no greater than twice the
- 9 diameter of said input luer; and,
- 10 a flow restrictor coupled to said filter housing.
  - 1 6. The aspiration tube assembly of claim 5, wherein
- 2 said input luer is pressed into said filter.
- The aspiration tube assembly of claim 5, wherein
- 2 said filter is pressed into said filter housing.
- 1 8. The aspiration tube assembly of claim 5, wherein
- 2 said flow restrictor has a diameter between 0.1 to 1
- 3 millimeters.
- 1 9. The aspiration tube assembly of claim 5, wherein
- 2 said flow restrictor is located within an output luer
- 3 attached to said filter housing.

- 10. The aspiration tube assembly of claim 9, wherein
- said output luer includes a scaling insert. 2
- 11. An aspiration tube assembly for a medical system, 1
- 2 comprising:

The Mr. Will fair that they they

- an input tube; 3
- an input luer coupled to said input tube; 4
- a filter housing coupled to said input luer; 5
- a filter located within said filter housing and pressed 6
- into said input luer; and,
- a flow restrictor coupled to said filter housing.
- The aspiration tube assembly of claim 11, wherein 12.
- said filter is pressed into said filter housing.
- The aspiration tube assembly of claim 11, wherein 1
- said flow restrictor has a diameter between 0.1 to 1 2
- 3 millimeters.
- The aspiration tube assembly of claim 11, wherein 14. 1
- said flow restrictor is located within an output luer 2
- attached to said filter housing.

BJY/wrj

- 1 15. The aspiration tube assembly of claim 14, wherein
- 2 said output luer includes a scaling insert.
- 1 16. A flow restrictor for a medical aspiration system,
- 2 comprising:
- 3 a filter housing;
- filter means for filtering a flow of fluid through said
- 5 filter housing; and,
- flow restrictor means for restricting the flow of fluid
- 7 through said filter housing.
- 1 17. The flow restrictor of claim 16, wherein said flow
- 2 restrictor means includes a flow restrictor with a diameter
- 3 between 0.1 to 1 millimeters.
- 1 18. The flow restrictor of claim 16, wherein said flow
- 2 restrictor means includes an output luer attached to said
- 3 filter housing.
- 1 19. The flow restrictor of claim 18, wherein said
- 2 output luer includes a scaling insert.

- 20. An aspiration tube assembly for a medical system, 1
- comprising: 2
- an input tube; 3
- a filter housing coupled to said input tube; 4
- filter means for filtering a flow of fluid through said 5
- filter housing; 6
- input means for coupling said input tube to said filter 7
- means; and 8

1

- flow restrictor means for restricting the flow of fluid through said filter housing.
  - The aspiration tube assembly of claim 20, wherein 21.
  - said input means includes an input luer that is pressed
  - into said filter means. 3
  - The aspiration tube assembly of claim 20, wherein 1
  - said filter means includes a filter that is pressed into
  - said filter housing. 3
  - The aspiration tube assembly of claim 20, wherein 1
  - said flow restrictor means includes a flow restrictor that 2
  - has a diameter between 0.1 to 1 millimeters.

BJY/wrj

- 1 24. The aspiration tube assembly of claim 20, wherein
- 2 said flow restrictor means includes an output luer attached
- 3 to said filter housing.
- 1 25. The aspiration tube assembly of claim 24, wherein
- 2 said output luer includes a scaling insert.
- 1 26. A method for aspirating a cornea, comprising:
- 2 inducing a flow of fluid out of the cornea;
- 3 filtering the fluid; and,
- 4 restricting the flow of filtered fluid.
- 1 27. The method of claim 26, further comprising
- 2 attaching a filter and a flow restrictor to an input tube
- 3 and an output tube.
- 1 28. The method of claim 27, further comprising
- 2 detaching the filter and the flow restrictor from the input
- 3 tube and the output tube.